

SWIFTHITCH²

SWIFTLY CONNECT TO TRAILED IMPLEMENTS AT UNBEATABLE SPEED.

Hustler's New SwiftHitch² provides the operator with better visibility, more manoeuvrability and easier connecting than any towbar quick hitch on the market which makes it easier to use and saves your precious time. And it doesn't stop there... it also has the strongest latching system providing more safety and you'll never need to get the grinder and welder out to replace a wear pad again!

NEW SwiftHitch² comes standard with a 40mm and 32mm pin, you choose which one you use and keep the other for a spare!

INDUSTRY BEST VISIBILITY

Cleanest and widest see-through tower on the market, and a clear view to the top of the pin.

STANDS BY ITSELF

Stands up on its own, making it easy to store, and connect to the tractor with huge lower linkage arm clearance. ISO standard hitch mounts ensure linkage arms go low enough to connect.

SELF-ALIGNING LATCH

Unique 'V' shape latch design that guides the pin under the towing eye making it easier to connect when slightly off centre.

TIGHTER TURNING

Allows full 90 degree turning when used with single post drawbar trailers - tightest turning angle of any hitch on the market, providing better manoeuvrability.

NEW STRONGER RHS BASE

The stronger RHS base with a diamond gusset is able to handle the heaviest loads. Our Series 2 is as strong as our SuperDuty model, but CAT 2 for versatility..

Replaceable wear pad & pin

Most other Quick Hitches on the market have wear pads that need to be cut off and re-welded on once worn out - this can be as frequent as once a year. Our replaceable Bis-alloy wear pad is simple to replace and saves you time and hassle.

NEW Unique pin shape

The new unique pin shape provides more articulation.

NEW CLEVIS HITCH MOUNTS

New stronger clevis plates, reinforced with gusset for ultimate strength and durability.

**5 YEAR
WARRANTY**

SAFEST LATCHING MECHANISM

Largest latching pin 3/4" to provide more reliability and loading. Latch covers more of the eye than others. Latch locks against the pin, making it impossible to accidentally disconnect, or a forced disconnection. Latching mechanism/lever is protected inside the main uprights for protection from damage and to eliminate accidental disconnection.

NEW 2 Pin Options

Comes standard with a 40mm and a 32mm pin, you choose which one you use and keep the other for a spare!



SPECIFICATIONS

CAPACITY: Up to 15 ton rating
TOW PIN: 32mm or 40mm
3PTL CLEVIS MOUNTS: CAT2

WEARPAD: Replaceable Bisalloy
LATCHING PIN: 3/4"
DRAWBAR LOAD: 4,000kg

HUSTLER®

SWIFTHITCH®

